



9301-E

Single gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 100

Closure Type:

Mounting Description: Metal ears

Box Type: Wall - Switch/Receptacle

Box Features: Metal ears

Installation Type: Old Work

Height: 3-1/4 in

Width: 2-3/8 in

Depth: 1-3/4 in

Volume: 9 cu in

Number of Gangs: 1

Product Info

Brand: fiberglassBOX

UPC: 85339100102

UNSPSC: 39121308

Carton Weight: 23 lbs

Carton Length: 20 in

Carton Width: 13 in

Carton Height: 8 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated carbon steel fasteners, Plated carbon steel clamp and fasteners

Features:

Machine tapped device holes, rectangular exterior, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, C2 clamps bulk packed

Application:

Old work residential construction 2 HR fire resistive walls and ceilings

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive

directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
