



9301-EC2

Single gang electrical box for use with nonmetallic

sheathed cable

Carton Quantity: 100

Closure Type:

Mounting Description: Metal ears
Box Type: Wall - Switch/Receptacle
Box Features: Wire clamps, Metal ears

Installation Type: Old Work

Height: 3-1/4 in Width: 2-3/8 in Depth: 1-3/4 in Volume: 9 cu in Number of Gangs: 1

Product Info

Brand: fiberglassBOX UPC: 85339100119 UNSPSC: 39121308

Carton Weight: 26 lbs Carton Length: 20 in Carton Width: 13 in Carton Height: 8 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Plated carbon steel clamp and

fasteners

Features:

Machine tapped device holes, rectangular exterior, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

Old work residential construction 2 HR fire resistive walls and ceilings

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 $\frac{1}{2}$ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes

and fittings classified for fire resistance)