



# 9327-N

Single gang electrical box for use with nonmetallic

sheathed cable

**Carton Quantity: 50** 

**Mounting Description:** Back nails **Box Type:** Wall - Switch/Receptacle

Box Features: Nails

Installation Type: New Work

Height: 3-5/8 in Width: 2-3/8 in Depth: 3-1/4 in Volume: 20.5 cu in Number of Gangs: 1

# **Product Info**

Brand: fiberglassBOX UPC: 85339101956 UNSPSC: 39121308 Carton Weight: 17 lbs Carton Length: 21 in

Carton Width: 10 in Carton Height: 11 in

Country of Origin: United States of America

Color: Off white

**Material:** Fiberglass reinforced polyester **Additional Materials:** Carbon steel fasteners

#### Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

## **Application:**

New work residential construction 2 HR fire resistive walls & ceilings used with QUICKFLASH for exterior stucco wall fixtures and outlets, UL approved for back-to-back

installation

#### Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

## **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

## Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)