



# 9368-EWK

Single gang electrical box for use with nonmetallic sheathed cable *Replacement for 9368-EW* 

**Carton Quantity: 100** 

Mounting Description: Metal wing brackets/nonmetal

ears wall compression

Box Type: Wall - Switch/Receptacle

Box Features: Metal ears, Speed "K" nonmetallic clamps,

Wing bracket

**Installation Type:** Old Work

Height: 3-1/4 in Width: 2-3/8 in Depth: 3-3/16 in Volume: 18 cu in Number of Gangs: 1

# **Product Info**

Brand: fiberglassBOX UPC: 85339760016 UNSPSC: 39121308 Carton Weight: 34 lbs

Carton Length: 21 in Carton Width: 13 in Carton Height: 14 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

#### Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

## **Application:**

Old work residential construction 2 HR fire resistive walls and ceilings

### Standards:

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

**Fire Test of Building Construction Materials** 

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

## Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)