



## Product Info

**Brand:** flexBOX

**UPC:** 85339249177

**UNSPSC:** 39121308

**Carton Weight:** 3 lbs

**Carton Length:** 9 in

**Carton Width:** 8 in

**Carton Height:** 6 in

**Country of Origin:** United States of America

**Color:** Black

**Material:** Polyvinyl Chloride

## P-108E

Single gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 24

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Nonmetal ears

**Installation Type:** Old Work

**Height:** 3-3/4 in

**Width:** 2-5/16 in

**Depth:** 1-1/4 in

**Volume:** 8 cu in

**Number of Gangs:** 1

### Features:

Molded-in spline device holes, rectangular exterior for easy cut-in

### Application:

Old work residential construction 2 HR fire resistive walls

### Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

### Fire Classification:

Fire Test of Building Construction Materials  
ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*