



## **P-108H**

Single gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 24

**Mounting Description:** Molded-in side mount hanger bracket

**Box Type:** Wall - Switch/Receptacle

**Installation Type:** New Work

**Height:** 3-3/4 in

**Width:** 2-5/16 in

**Depth:** 1-1/4 in

**Volume:** 8 cu in

**Number of Gangs:** 1

## **Product Info**

**Brand:** flexBOX

**UPC:** 85339249184

**UNSPSC:** 39121308

**Carton Weight:** 3 lbs

**Carton Length:** 11 in

**Carton Width:** 8 in

**Carton Height:** 6 in

**Country of Origin:** United States of America

**Color:** Black

**Material:** Polyvinyl Chloride

### **Features:**

Molded-in splined device holes

### **Application:**

New work residential construction 2 HR fire resistive walls & ceilings

### **Standards:**

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**⚠ WARNING - PROP 65**  
[Click here for more information!](#)

### **Fire Classification:**

Fire Test of Building Construction Materials  
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### **Fire Resistance Classification in Wall Assemblies 2-Hours or less**

Shall be separated by a horizontal distance of not less than 24 inches

### **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less**

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---