



P-1220W

Single gang electrical box for use with nonmetallic

sheathed cable

Carton Quantity: 48

Mounting Description: Metal wing brackets/nonmetal

ears wall compression

Box Type: Wall - Switch/Receptacle

Box Features: Nonmetal ears, Wing bracket

Installation Type: Old Work

Height: 3-3/4 in **Width:** 2-5/16 in **Depth:** 3-3/4 in **Volume:** 22.5 cu in

Number of Gangs: 1

Product Info

Brand: flexBOX UPC: 85339249139 UNSPSC: 39121308 Carton Weight: 14 lbs Carton Length: 24 in

Carton Width: 10 in Carton Height: 8 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polyvinyl Chloride

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners

Features:

Molded-in spline device holes, rectangular exterior for easy cut-in

Application:

Old work residential construction 2 HR fire resistive walls

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)