



## Product Info

**Brand:** flexBOX

**UPC:** 85339249146

**UNSPSC:** 39121309

**Carton Weight:** 9 lbs

**Carton Length:** 18 in

**Carton Width:** 16 in

**Carton Height:** 10 in

**Country of Origin:** United States of America

**Color:** Black

**Patents:** U.S. Patent No. 8,143,518

**Material:** Polyvinyl Chloride

**Additional Materials:** Carbon steel fasteners

## P-122SC

Single gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 24

**Mounting Description:** Angled mid nails with two optional bottom mount recessed buttons

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Nails

**Installation Type:** New Work

**Height:** 3-3/4 in

**Width:** 2-9/32 (5-1/2) in

**Depth:** 1-3/4 in

**Volume:** 23.5 cu in

**Number of Gangs:** 1

### Features:

Molded-in splined device holes, offset gauge marks, leveling ribs, cover and pocket for additional cubic inch fill in shallow walls

### Application:

New work residential construction 2 HR fire resistive walls (shallow 1" x 2") & ceilings

### Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

### Fire Classification:

Fire Test of Building Construction Materials  
ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---