ALLIED MOULDED PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506

P-181

Single gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 125
Mounting Description: Angled mid nails
Box Type: Wall - Switch/Receptacle
Box Features: Nails
Installation Type: New Work
Height: 3-3/4 in
Width: 2-5/16 in
Depth: 2-5/8 in
Volume: 18 cu in
Number of Gangs: 1

Product Info

Brand: flexBOX
UPC: 85339243915
UNSPSC: 39121308
Carton Weight: 26 lbs
Carton Length: 12 in
Carton Width: 22 in
Carton Height: 22 in
Country of Origin: United States of America
Color: Black
Material: Polyvinyl Chloride
Additional Materials: Carbon steel fasteners

Features:

Molded-in splined device holes, offset gauge marks, leveling ribs

Application:

New work residential construction 2 HR fire resistive walls & ceilings

Standards:

ANSI / UL 514C: File No. E30594

UL LISTED

WARNING – PROP 65
Click here for more information!

Fire Classification:

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)