



**ALLIED  
MOULDED  
PRODUCTS, Inc.**

**419-636-4217  
222 N. Union St.  
Bryan, OH 43506**



## Product Info

**Brand:** flexBOX

**UPC:** 85339249078

**UNSPSC:** 39121308

**Carton Weight:** 12 lbs

**Carton Length:** 20 in

**Carton Width:** 13 in

**Carton Height:** 9 in

**Country of Origin:** United States of America

**Color:** Black

**Material:** Polyvinyl Chloride

**Additional Materials:** Galvanized snap in bracket

## P-241H

Single gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 50

**Mounting Description:** Molded-in side mount hanger bracket

**Box Type:** Wall - Switch/Receptacle

**Box Features:** "HL" hanger

**Installation Type:** New Work

**Height:** 3-3/4 in

**Width:** 2-5/16 in

**Depth:** 3-9/16 in

**Volume:** 24 cu in

**Number of Gangs:** 1

### Features:

Molded-in splined device holes, leveling ribs

### Application:

New work residential construction 2 HR fire resistive walls & ceilings

### Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**⚠ WARNING - PROP 65**

[Click here for more information!](#)

### Fire Classification:

Fire Test of Building Construction Materials  
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---