



Product Info

Brand: flexBOX

UPC: 85339249047

UNSPSC: 39121308

Carton Weight: 27 lbs

Carton Length: 22 in

Carton Width: 13 in

Carton Height: 16 in

Country of Origin: United States of America

Color: Black

Material: Polyvinyl Chloride

Additional Materials: Carbon steel fasteners, Galvanized snap in bracket

P-241QT

Single gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 100

Closure Type:

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

Box Features: Nails

Installation Type: New Work

Height: 3-3/4 in

Width: 2-5/16 in

Depth: 3-9/16 in

Volume: 24 cu in

Number of Gangs: 1

Features:

Quick Thread device holes, offset gauge marks, leveling ribs

Application:

New work residential construction 2 HR fire resistive walls & ceilings

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials
ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes

and fittings classified for fire resistance)
