



## 3300-2Z2K

Three gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 25

**Mounting Description:** Stud mount "Z" hanger bracket both sides with 1/4" offset

**Box Type:** Wall - Switch/Receptacle

**Box Features:** "Z" hanger(s), Speed "K" nonmetallic clamps

**Installation Type:** New Work

**Height:** 3-3/4 in

**Width:** 5-11/16 in

**Depth:** 3 in

**Volume:** 46 cu in

**Number of Gangs:** 3

## Product Info

**Brand:** fiberglassBOX

**UPC:** 85339147022

**UNSPSC:** 39121308

**Carton Weight:** 29 lbs

**Carton Length:** 20 in

**Carton Width:** 15 in

**Carton Height:** 15 in

**Country of Origin:** United States of America

**Color:** Off white

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated carbon steel fasteners, Polyvinyl chloride clamps

## Features:

Machine tapped device holes, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

## Application:

New work residential construction stud face mounted 2 HR fire resistive walls

## Standards:

ANSI / UL 514C: [File No. E30594](#)



## Fire Classification:

### Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*