



# 3300-Z2K

Three gang electrical box for use with nonmetallic sheathed cable *Replacement for 3300-Z2* 

**Carton Quantity: 25** 

Mounting Description: Stud mount "Z" hanger bracket

with 1/4" offset

Box Type: Wall - Switch/Receptacle

**Box Features:** "Z" hanger(s), Speed "K" nonmetallic

clamps

**Installation Type:** New Work

Height: 3-3/4 in Width: 5-11/16 in Depth: 3 in Volume: 46 cu in Number of Gangs: 3

## **Product Info**

**Brand:** fiberglassBOX **UPC:** 85339145622

UNSPSC: 39121308 Carton Weight: 24 lbs Carton Length: 19 in

Carton Width: 13 in Carton Height: 13 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

#### Features:

Machine tapped device holes, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps

factory installed

#### **Application:**

New work residential construction stud face mounted 2 HR fire resistive walls

#### Standards:

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)