



## 3303-NKV

Three gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 18

**Closure Type:**

**Mounting Description:** Angled mid nails

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Nails, Speed "K" nonmetallic clamps, Air-sealed flange (energy efficient)

**Installation Type:** New Work

**Height:** 3-3/4 in

**Width:** 5-11/16 in

**Depth:** 3-9/16 in

**Volume:** 56.5 cu in

**Number of Gangs:** 3

## Product Info

**Brand:** Vapor Seal

**UPC:** 85339152095

**UNSPSC:** 39121308

**Carton Weight:** 17 lbs

**Carton Length:** 20 in

**Carton Width:** 16 in

**Carton Height:** 8 in

**Country of Origin:** United States of America

**Color:** Off white

**Patents:** U.S. Patent No. 6,908,003 B2

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Carbon steel fasteners, Polyvinyl chloride clamps, Polyurethane flange

## Features:

Polyurethane flange for single drywall offset, machine tapped device holes, slot provision for low voltage divider, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

## Application:

New work residential construction 2 HR fire resistive walls - air-sealed electrical boxes for envelope walls in Energy Star homes

## Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

NEMA OS 4 - Energy Efficient Air-Sealed Boxes for Electrical Applications



## Fire Classification:

**Fire Test of Building Construction Materials**

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

**Fire Resistance Classification in Wall Assemblies 2-Hours or less**

Shall be separated by a horizontal distance of not less than 3 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---