



# P-643

Three gang electrical box for use with nonmetallic

sheathed cable

**Carton Quantity: 20** 

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

Box Features: Nails

Installation Type: New Work

Height: 3-3/4 in Width: 5-13/16 in Depth: 3-9/16 in Volume: 63 cu in Number of Gangs: 3

# **Product Info**

Brand: flexBOX UPC: 85339463023 UNSPSC: 39121308 Carton Weight: 9 lbs Carton Length: 19 in

Carton Width: 13 in Carton Height: 13 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Carbon steel fasteners

#### Features:

Molded-in splined device holes, offset gauge marks, leveling ribs

# **Application:**

New work residential construction 2 HR fire resistive walls

## Standards:

ANSI / UL 514C: File No. E30594



## Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)