



9329-EWK

Two gang electrical box for use with nonmetallic sheathed

cable

Carton Quantity: 50

Mounting Description: Metal wing brackets/metal ears

wall compression

Box Type: Wall - Switch/Receptacle

Box Features: Metal ears, Speed "K" nonmetallic clamps,

Wing bracket

Installation Type: Old Work

Height: 3-1/4 in Width: 4-1/8 in Depth: 3-1/4 in Volume: 32.5 cu in Number of Gangs: 2

Product Info

Brand: fiberglassBOX **UPC:** 85339108023

UNSPSC: 39121308 Carton Weight: 27 lbs

Carton Length: 19 in Carton Width: 9 in Carton Height: 17 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

Old work residential construction 2 HR fire resistive walls

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)