



Product Info

Brand: fiberglassBOX

UPC: 85339106838

UNSPSC: 39121309

Carton Weight: 26 lbs

Carton Length: 17 in

Carton Width: 12 in

Carton Height: 16 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyvinyl chloride clamps

9372-NMHK

Two gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 48

Closure Type:

Mounting Description: Angled mid nails with 3/16" panel stops opposite side

Box Type: Wall - Switch/Receptacle

Box Features: Speed "K" nonmetallic clamps, Nails

Installation Type: New Work

Height: 3-3/4 in

Width: 4 in

Depth: 2-3/4 in

Volume: 30 cu in

Number of Gangs: 2

Features:

Machine tapped device holes, 3/16" panel stops, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

Manufactured housing construction 2 HR fire resistive walls

Standards:

ANSI / UL 514C: [File No. E30594](#)



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)