ALLIED MOULDED PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506

P-442

Two gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 48
Mounting Description: Angled mid nails
Box Type: Wall - Switch/Receptacle
Box Features: Nails
Installation Type: New Work
Height: 3-3/4 in
Width: 4 in
Depth: 3-9/16 in
Volume: 43 cu in
Number of Gangs: 2

Product Info

Brand: flexBOX
UPC: 85339440000
UNSPSC: 39121308
Carton Weight: 17 lbs
Carton Length: 17 in
Carton Width: 17 in
Carton Height: 15 in
Country of Origin: United States of America
Color: Black
Patents: U.S. Patent No. 6,365,831 B1
Material: Polycarbonate
Additional Materials: Carbon steel fasteners

Features:

Molded-in splined device holes, offset gauge marks, leveling ribs

Application:

New work residential construction 2 HR fire resistive walls

Standards:

ANSI / UL 514C: File No. E30594

UL LISTED

Fire Classification:

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less
Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)