



## **P-442HQT**

Two gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 48

**Closure Type:**

**Mounting Description:** Stud face mount steel hanger bracket with 1/2" offset and opposite side drywall tabs

**Box Type:** Wall - Switch/Receptacle

**Box Features:** "HL" hanger

**Installation Type:** New Work

**Height:** 3-3/4 in

**Width:** 4 in

**Depth:** 3-9/16 in

**Volume:** 43 cu in

**Number of Gangs:** 2

## **Product Info**

**Brand:** flexBOX

**UPC:** 85339440031

**UNSPSC:** 39121308

**Carton Weight:** 20 lbs

**Carton Length:** 18 in

**Carton Width:** 16 in

**Carton Height:** 15 in

**Country of Origin:** United States of America

**Color:** Black

**Patents:** U.S. Patent No. 6,365,831 B1

**Material:** Polycarbonate

**Additional Materials:** Galvanized snap in bracket

### **Features:**

Quick Thread device holes, leveling ribs

### **Application:**

New work residential construction 2 HR fire resistive walls

### **Standards:**

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**⚠ WARNING - PROP 65**  
[Click here for more information!](#)

### **Fire Classification:**

#### **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### **Fire Resistance Classification in Wall Assemblies 2-Hours or less**

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes*

*and fittings classified for fire resistance)*

---