



# **P-442HQT**

Two gang electrical box for use with nonmetallic sheathed

cable

**Carton Quantity: 48** 

**Closure Type:** 

**Mounting Description:** Stud face mount steel hanger bracket with 1/2" offset and opposite side drywall tabs

Box Type: Wall - Switch/Receptacle

**Box Features:** "HL" hanger **Installation Type:** New Work

Height: 3-3/4 in Width: 4 in Depth: 3-9/16 in Volume: 43 cu in

Number of Gangs: 2

# **Product Info**

Brand: flexBOX UPC: 85339440031 UNSPSC: 39121308 Carton Weight: 20 lbs Carton Length: 18 in

Carton Width: 16 in Carton Height: 15 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Galvanized snap in bracket

#### Features:

Quick Thread device holes, leveling ribs

## **Application:**

New work residential construction 2 HR fire resistive walls

### Standards:

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)