419-636-4217
222 N. Union St.
Bryan, OH 43506

P-442QT

Two gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 48

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

Box Features: Nails

Installation Type: New Work

Height: 3-3/4 in

Width: 4 in

Depth: 3-9/16 in

Volume: 43 cu in

Number of Gangs: 2

Product Info

Brand: flexBOX

UPC: 85339440017

UNSPSC: 39121308

Carton Weight: 16 lbs

Carton Length: 17 in

Carton Width: 17 in

Carton Height: 15 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Carbon steel fasteners, Galvanized snap in bracket

Features:

Quick Thread device holes, offset gauge marks, leveling ribs

Application:

New work residential construction 2 HR fire resistive walls

Standards:

ANSI / UL 514C: File No. E30594

LISTED

WARNING – PROP 65
Click here for more information!

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive

directory and Allied Moulded’s CEYY.9379 (Outlet boxes and fittings classified for fire resistance)