



## Product Info

**UPC:** 85339095002

**UNSPSC:** 39121309

**Carton Weight:** 12 lbs

**Carton Length:** 21 in

**Carton Width:** 10 in

**Carton Height:** 11 in

**Country of Origin:** United States of America

**Color:** Beige

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Nonmetallic pop-in cable clamp

**Box Diameter:** 4

## AC9500

4" dia. round fixture support box with 7" square mounting flange for use with nonmetallic sheathed cable

**Carton Quantity:** 20

**Mounting Description:** Back side mount with fasteners

**Installation Type:** New Work

**Width:** 4 in

**Depth:** 1-1/4 in

**Volume:** 12 cu in

**Fixture Rating:** 15lbs

## Features:

Machine tapped fixture holes, "pop-in" cable clamp, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

## Application:

Residential home - exterior light fixture electrical box (15 lb fixture rating) for use with nonmetallic sheathed cable

**Box Diameter:** 4

## Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

## Fire Classification:

Fire Test of Building Construction Materials  
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

## Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---