



**ALLIED
MOULDED
PRODUCTS, Inc.**

**419-636-4217
222 N. Union St.
Bryan, OH 43506**



Product Info

UPC: 85339095002

UNSPSC: 39121309

Carton Weight: 12 lbs

Carton Length: 21 in

Carton Width: 10 in

Carton Height: 11 in

Country of Origin: United States of America

Color: Beige

Material: Fiberglass reinforced polyester

Additional Materials: Nonmetallic pop-in cable clamp

Box Diameter: 4

AC9500

4" dia. round fixture support box with 7" square mounting flange for use with nonmetallic sheathed cable

Carton Quantity: 20

Mounting Description: Back side mount with fasteners

Installation Type: New Work

Width: 4 in

Depth: 1-1/4 in

Volume: 12 cu in

Fixture Rating: 15lbs

Features:

Machine tapped fixture holes, "pop-in" cable clamp, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

Residential home - exterior light fixture electrical box (15 lb fixture rating) for use with nonmetallic sheathed cable

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

⚠ WARNING - PROP 65

[Click here for more information!](#)

Fire Classification:

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Fire Resistance Classification in Floor-Ceiling

Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
