

# Type 5305–NK

File Number: R9379

## COMPANY

### ALLIED MOULDED PRODUCTS INC

222 N UNION ST

BRYAN, OH 43506–1450 United States

## TYPE INFO

5305–NK

Nonmetallic outlet and switch boxes

## HOURLY RATINGS AND USE

Classification Period	Additional Information
2	For use in fire resistance walls constructed of min. 5–1 / 2 in. deep wood or nonbearing steel studs and gypsum wallboard and gypsum board with Classification periods of 2 hrs or less. Clearance between boxes and cutouts in wall shall not exceed 1 / 8 in. The area of openings for boxes shall not aggregate more than 100 sq in. per 100 sq ft of wall or partition area with no opening exceeding 35.2 sq in. Outlet boxes on opposite sides of wall or partition may be installed back to back.

Report Date: 2025–06–11  
Revision Date: 2025–09–22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow – Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow – Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non–misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."