ISSUE DATE: .56 [14.30] → ← 6.72 [170.69] → 3.99 [101.22] .76 [19.41] -> OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM В 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS (2) POLYCARBONATE FLANGES (GLUED) 6.50 [165.10] .10 [2.54] 3.50 [88.90] 7.63 [193.79] **BACK VIEW** 3.99 [101.32] (4) EACH #10-32 BRASS INSERTS, AND STAINLESS STÉEL FLANGE AND **FEET SCREWS** 6.75 [171.44] → 5.18 [131.47] < 3.50 [88.90] SLOT 6.88 [174.74] MAX STAINLESS STEEL DIST (8) R.162 [4.102] **SLOT** HINGE PIN DIST FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL 4.00 [101.60] NONMETALLIC NEOPRENE → 4.81 [122.24] < LOCKABLE SNAP LATCH **GASKET** LOCATED ON CENTER 6.04 [153.40] - .13 [3.30] 4.81 [122.24] 4.25 [107.95] (4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664NLWF THIS MATERIAL IS OWNED BY THE ALLIED MOULDED

CLEAR COVER AND WINDOWS- POLYCARBONATE

PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.