ISSUE DATE: .56 [14.30] - 6.72 [170.69] -3.99 [101.22] .76 [19.41] -> OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM (2) POLYCARBONATE В 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS FLANGES (GLUED) 6.50 [165.10] .10 [2.54] 3.50 [88.90] 7.63 [193.79] (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS STEEL FLANGE AND **BACK VIEW** 3.99 [101.32] **FEET SCREWS** 6.75 [171.44] 5.18 [131.47] SLOT 6.88 [174.74] 3.50 [88.90] MAX DIST (8) R.162 [4.102] **SLOT** STAINLESS STEEL **HINGE PIN** DIST FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL-NEOPRENE 4.00 [101.60] STAINLESS STEEL LOCKABLE TWIST LATCH → 4.81 [122.24] <del><</del> **GASKET** LOCATED ON CENTER 6.04 [153.40] - .13 [3.30] 4.81 [122.24] 4.25 [107.95] (4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [ 107.95 ] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664TWF THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED CLEAR COVER AND WINDOWS- POLYCARBONATE WITHOUT PRIOR WRITTEN PERMISSION FROM

ALLIED MOULDED PRODUCTS.